

PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW GLOSS OIL PAINT

Rev. 2 T.D.S.

DESCRIPTION

A premium quality, alkyd enamel that resists chalking and fading. EdgeChem Color Glow Gloss Oil Paint formulated to give even flow and leveling resulting in a uniform, full gloss finish which weathers extremely well. It is easy to use and provides excellent protection against tropical weather conditions.

PERFORMANCE FEATURES

- Tough finish providing excellent exterior protection especially for wood and metal surfaces
- Fungus and mildew resistant
- Interior and exterior use
- Low odour
- Beautiful and durable high gloss finish.

PHYSICAL PROPERTIES

Gloss	:	>85°/60°
Viscosity	:	1000-1500 cPs
Specific Gravity	:	1.1-1.2
Flash Point	:	42°C
Drying Time (31° and 70% RH):-		
To Touch	:	4 hours
To Re-coat	:	24 hours
Colours	:	White, Black, Tile Red, Dusty Grey, Regatta, Morning Glory, Turf Green, Mint Green, Aquamarine, Pewter, Ash Grey, Off White, Antique, Gardenia, Sundance Yellow, Paw Paw, Teenage Pink, Fiesta Red, Golden Brown, Spanish Brown


COVERAGE RATE

Approximately 10 m² per/L (400 sq. ft/gallon) @:

- 4.0 mils wet film thickness
- 2.0 mils dry film thickness (**dependent on porosity of surface**).

SURFACE PREPARATION

Surface must be free of dirt, chalk, wax, rust, mildew, fungus and all other foreign substances. Glossy surfaces should be sanded. New or unpainted surfaces such as steel, iron, aluminum and concrete should be primed using appropriate primer. Color Glow Gloss is self-priming on bare wood.



PRODUCT DATA SHEET

EDGE CHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

COLOR GLOW GLOSS OIL PAINT

Rev. 2

T.D.S.

APPLICATION

Stir thoroughly before use. If using a brush or roller thinning is not required. If spraying, reduce by 10% using EdgeChem Oil Paint Reducer (**1 pint reducer to 1 gallon paint**). Paint spatters or drops must be cleaned immediately with the reducer.

SHELF LIFE

3 years

CLEAN-UP

Clean brushes, roller and spray equipment immediately after use with EdgeChem Oil Paint Reducer.

