

PRODUCT DATA SHEET

EDGECEM JAMAICA LIMITED
 18 Carifta Avenue
 Kingston 11, Jamaica
 Tel: (876) 937-3831-4 Fax: 937-3838
 E-mail: edge@cwjamaica.com

EDGEKOTE Veneer Wall Plaster

Rev. 0 P.D.S.

DESCRIPTION

EDGEKOTE is a premium quality acrylic masonry/cementitious filler designed to fill nail holes, cracks and open seams on all properly prepared interior/exterior masonry, cement board and wooden surfaces. Edgekote gives a hard, smooth, even and non-porous finish, with good alkali, molds, mildew and water resistant.

PERFORMANCE FEATURES

- Premium quality acrylic masonry/cementitious filler
- Very good alkali, molds, mildew and Water Resistant.
- Interior/exterior water-based 100% powder product.
- Gives a hard, smooth, even and non-porous flat finish.
- Repair properly prepared masonry, cement board and wooden surfaces.
- Easy to mix/apply and fills small holes, cracks and open seams.

PHYSICAL PROPERTIES

Colour	:	Light Cream
Finish	:	Flat
Gloss	:	≤ 5° @ 85°
Viscosity	:	Powder
Flash Point	:	Non-Flammable
Weight by Solids	:	100%

SURFACE PREPARATION

Surface must be properly;

CLEAN i.e. Free of contaminants (dirt, grease, wax, rust, mildew, fungus, chalking, efflorescence and peeling/loose paint) that can negatively affect optimal bonding.

DRY i.e. Surface should be dry (moisture-free).

DULL i.e. Surface should be de-glossed / flattened (glossy surface must be sanded).


NB To improve adhesion and for ease of application, prepare a 'V' groove for cracks. Please wear appropriate safety gears while carrying-out surface preparation or application.

11/2018

06

EDGECEM JAMAICA LIMITED

The suggestions, recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use or our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent



PRODUCT DATA SHEET

EDGECEM JAMAICA LIMITED
 18 Carifta Avenue
 Kingston 11, Jamaica
 Tel: (876) 937-3831-4 Fax: 937-3838
 E-mail: edge@cwjamaica.com

EDGEKOTE Veneer Wall Plaster

Rev. 0 P.D.S.

SUGGESTED USES

Recommended to be applied on properly prepared masonry, concrete, cement board and wooden surfaces.

MIXING

- Mix EDGEKOTE Veneer Wall Plaster in container with clean water
- Mixing ratio – 3 parts Powder(filler) : 2 parts Water
- Hand-mix with plastic spreader/putty knife to a smooth-paste. **(SMALL JOB)**
- Mix with heavy duty drill and paint mixing paddle @ ≥ 650rpm for ~ 5 minutes.
- **Remember** – only mix material than can be applied within 45 minutes, as re-dispersing with additional water can have negative effects with finish product.

APPLICATION

- Apply each coat @ 1mm – 3mm (**Remember**- allow each coat to dry adequately).
- Apply first coat of mix product firmly to voids, holes or seams on substrate.
- Apply the second coat and smoothen to a thickness ≥ 1.5mm but ≤ 5.0mm.

NB

Removing excess product immediately after application can improve sanding and drying performance.

DRYING TIME

@ 25° and 70% RH

To Touch : ~ 30 minutes (Dependent on film thickness, temperature and relative humidity)

To Recoat : After 2 hours (Dependent on film thickness, temperature and relative humidity)

To Sand : Up to 24 hours (Dependent on film thickness, temperature and relative humidity)

SHELF LIFE

12 months in original unopened container

CLEAN-UP

Clean applicator tools and equipment immediately after application with soap and clean water.

PRECAUTIONS

Product is not recommended to be used on hot surfaces, direct sunlight or overcast condition. These factors can impact negatively on the performance such as drying and cause cracking. Product contain Portland cement which can be a skin irritant, therefore appropriate care must be taken by wearing dust mask, safety eyewear, rubber gloves and appropriate clothing while mixing or using this product.

11/2018

07

EDGECEM JAMAICA LIMITED

The suggestions, recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use or our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent