

# TCHNICAL DATA SHEET

## **Auto Prime Filler**

### Description

Auto Prime Filler is a quick drying acrylic urethane 2 pack primer surfacer designed to give superior filling properties. Excellent adhesion and colour/gloss hold out

### **Compatible Substrates**

Properly prepared steel substrate. Wash primers and etching primer. Putties polyester fillers and body filler

### Preparation

Existing finish - degrease, dry flat with P180-P280 Wet flat with P400 sandpaper Polyester filler - degrease, dry flat with P180 Adjacent area dry flat with P280 Steel surface - degrease, dry flat with P180

### Application

2-3 wet coats allowing 5-10 minutes flash time HLVP 7-8 psi @ at the air cap Conventional 30-35 psi at the s/gun inlet Spray gun set up fluid tip 1.5 – 2.0 mm



### Properties

VOC - 280 G/L or2.33lbs/gal Shelf life - 2 years Colours - light grey Coverage rate - 400-450 ft<sup>2</sup>/gal @ 2.0 – 3.0 mil DFT Flash point - 25 <sup>°</sup>C

### Limitations:

Edgechem products should not be combined with components of other product lines.

### Precautionary Information:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have hazards of all its parts. Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Follow label directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

#### Medical Response:

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (876)937-3831-4

### Material Safety Data Sheet:

Material safety data sheet for the Edgechem products named herein can be obtained from Edgechem Jamaica Limited by emailing researchanddev@edgechem.com