



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 3

T.D.S.

COLOR GLOW CLASSIC WHITES FLAT EMULSION

DESCRIPTION

Color Glow Classic Whites Flat Emulsion is a premium quality paint for both indoor and outdoor use. Its subtle tones and soothing hues add class to your décor and comfort to your living. It is easy to apply, fungus and stain resistant and carries very little odour.

PERFORMANCE FEATURES

- Interior & exterior durability
- Non-toxic
- Resistant to fungus, mildew and weathering
- Very low odour
- Easy application
- Excellent scrubbability
- High hiding
- Excellent color retention
- Resistant to cracking and peeling

PHYSICAL CHARACTERISTICS

| | | |
|------------------------------|---|---------------------------------------------------------------------------|
| Colour | : | Icicle, Honeydew, Honey White, Caress, Silver Spray, Apple White |
| Finish | : | Flat |
| Gloss | : | $\leq 5^\circ/85^\circ$ |
| Viscosity | : | ~ 5500 cPs |
| Flash Point | : | Water-based |
| Drying Time (31° and 70% RH) | | |
| To Touch | : | approximately 15 minutes (Dependent on temperature and relative humidity) |
| To Recoat | : | after 1 hour |

COVERAGE RATE

Approximately 400 ft²/gallon at 1.5 mils DFT dependent on surface porosity.

04/2022

EDGECHEM JAMAICA LIMITED

The suggestions recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use of our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.

COLOR GLOW CLASSIC WHITES FLAT EMULSION

SUGGESTED USES

On properly primed surfaces including wood, vinyl, aluminum, drywall, wood trim, window masonry, galvanized and ferrous metal.

SURFACE PREPARATION

Surface must be free of dirt, grease, wax, rust, mildew, fungus, chalk and peeling paint. Glossy surface should be sanded. Check adhesion to suspected alkyd or oil paint in an area prior to applying latex coatings. If an adhesion problem is present, prime with a suitable primer to form an intermediate coat. New or unpainted surfaces should be cured properly then coated with 1 coat of EDGECHEM CONCRETE SEALER before application.

APPLICATION

Stir Color Glow classic Whites Flat Emulsion thoroughly before application. If using a brush or roller no reduction is required – use full body. If necessary, thin with water, no more than ½ pint per gallon. If spraying, reduction of up to 1 pint of water per gallon is allowed. Spatters should be removed immediately with clean water. Dries in approximately fifteen minutes. Recoatable after one hour.

SHELF LIFE

2 Years

CLEAN-UP

This should be done immediately using clean water. Wash out brushes, rollers and hands immediately after painting.