



EDGECEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: edge@cwjamaica.com  
Website: www.edgechem.com

## PRODUCT DATA SHEET

Rev. 2

T.D.S.

### COLOR GLOW FLAT EMULSION

#### DESCRIPTION

Color Glow Flat Emulsion is a quality styrene acrylic paint designed for long term durability on a variety of interior and exterior surfaces. Its excellent properties and low cost makes it the best value for money paint available.

#### PERFORMANCE FEATURES

- Interior & exterior durability
- Non-toxic
- Resistant to fungus, mildew and weathering
- Very low odour
- Easy application
- Excellent scrubbability
- High hiding
- Excellent color retention
- Resistant to cracking and peeling

#### PHYSICAL CHARACTERISTICS

|                                       |   |   |
|---------------------------------------|---|---|
| Colour                                | : | White, Off-White, Gardenia, Teenage Pink, Morning Glory<br>Mint Green, Ash Grey, Dusty Grey, Aquamarine, Paw Paw<br>Whisper, Warm Cream, Raspberry, Sunshine Yellow<br>Bone White, Olive Green, Surf Blue, Lilac, Black, Blue<br>Blossom, Blue Lagoon, Harvest Yellow, Mango Squash, Hot<br>Sauce |
| Specific Gravity (g/cm <sup>3</sup> ) | : | 1.3 ± 0.1   |
| Finish                                | : | Flat  |
| Gloss                                 | : | ≤ 5%/85°  |
| Viscosity                             | : | ~ 5500 cPs  |
| Flash Point                           | : | Water-based   |
| Drying Time (31° and 70% RH)          | : |   |
| To Touch                              | : | approximately 15 minutes (Dependent on temperature and relative humidity)   |
| To Recoat                             | : | after 1 hour  |

## COLOR GLOW FLAT EMULSION

### COVERAGE RATE

Approximately 400 ft<sup>2</sup>/gallon at 1.5 mils DFT dependent on surface porosity.

### SUGGESTED USES

On properly primed surfaces including wood, vinyl, aluminum, drywall, wood trim, window masonry, galvanized and ferrous metal.

### SURFACE PREPARATION

Surface must be free of dirt, grease, wax, rust, mildew, fungus, chalk and peeling paint. Glossy surface should be sanded. Check adhesion to suspected alkyd or oil paint in an area prior to applying latex coatings. If an adhesion problem is present, prime with a suitable primer to form an intermediate coat. New or unpainted surfaces should be cured properly then coated with 1 coat of EDGECHEM CONCRETE SEALER before application.

### APPLICATION

Stir Color Glow Flat Emulsion thoroughly before application. If using a brush or roller no reduction is required – use full body. If necessary, thin with water, no more than ½ pint per gallon. If spraying, reduction of up to 1 pint of water per gallon is allowed.

### SHELFLIFE

2 years

### CLEAN-UP

This should be done immediately using clean water. Wash out brushes, rollers and hands immediately after painting.