



EDGECHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

## PRODUCT DATA SHEET

Rev. 3

T.D.S.

### COLOR GLOW ACRYLIC TEXTURE (TROWEL GRADE)

#### DESCRIPTION

Color Glow Textured Paint is a very flexible, high density coating with a distinctively rough surface and high build. It can be used for both interior and exterior applications to provide aesthetic appeal and long-lasting protection.

#### PERFORMANCE FEATURES

- Excellent adhesion
- Excellent hiding (masks surface defects)
- High build
- Superior flexibility
- Tough stone-like finish
- Impervious to water and moisture
- Mildew and fungus resistant
- Non-toxic
- Interior and exterior durability

#### PHYSICAL PROPERTIES

Colour	:	Customer specified
Specific gravity (g/cm <sup>3</sup> )	:	~1.45 (~12lb/gal)
Drying Time (31° and 70% RH)		
To Touch	:	1 hour
Hard dry	:	24 hours

#### COVERAGE RATE

Approximately 80-100 ft<sup>2</sup> per pail depending on grade and application.

## **COLOR GLOW ACRYLIC TEXTURE**

### **SUGGESTED USES (SUITABLE SUBSTRATE)**

All concrete surfaces\* (poured, stucco precast, rendered or previously painted), plywood, and dry wall.

**\* It is not recommended to use trowable paint on rough cast concrete. If this is the case it is recommended to do a 'one coat wood float finish on the concrete blocks before application.**

### **SURFACE PREPARATION**

Ensure that surfaces are clean, dry and free from grease and loose sand or debris. Previously painted surfaces must be checked for chalking. Remove all loose paint before application.

For previously painted surfaces where there may be chalking, power wash is recommended in which the substrate should be left to dry for three (3) days before application of the Trowel-on

Newly cast concrete wall should be left to dry at minimum thirty (30) days before application.

### **APPLICATION**

Stir paint thoroughly to ensure coarse material is distributed evenly throughout the paint. No reduction is necessary.

For a trowel finish using a clean steel float spread small amounts of paint evenly over prepared surface. Allow to set for 15-30 minutes, depending on climatic conditions. Using a plastic trowel, create the desired effect working in a circular motion, preferably in a clockwise direction (clean surface of float with water periodically).

**NOTE:** Trowel finishes can be repainted with regular paint by using a brush or a fluffy roller. Thus repaint is possible and the pattern will not be lost.

### **SHELF LIFE**

2 years

### **CLEAN UP**

Using clean water, wash all tools, hands and clothes immediately after application.