

EDGECHEM JAMAICA LIMITED 18 Carifta Avenue Kingston 11, Jamaica Tel: (876) 937-3831-4 Fax: 937-3838 E-mail: edge@cwjamaica.com Website: www.edgechem.com

# **PRODUCT DATA SHEET**

Rev. 3 T.D.S.

# **COLOUR GLOW PLUS Gloss Oil Paint**

# **DESCRIPTION**

A Premium quality alkyd enamel that resist chalking and fading. Edgechem Color Glow Plus Gloss Oil Paint Formulated to give even flow and leveling resulting in a uniform, full gloss finish which weathers extremely well. It is easy to use and provides excellent protection against tropical weather conditions.

## PERFORMANCE FEATURES

- Tough finish providing excellent exterior protection especially for wood and metal surfaces
- Fungus and mildew resistant
- Interior and exterior use
- Low odour
- Beautiful and durable high gloss finish.

## PHYSICAL PROPERTIES

Gloss	:	>85% /60°
Viscosity	:	800-1000 cPs
Specific Gravity	:	1.1-1.2
Flash Point	:	42°C
Drying Time (31° and	70% RH)	
To Touch		: 4 hours
To Recoat		: 24 hours
Colours		: White, Black, Tile Red, Dusty Grey, Regatta, Morning Glory, Turf

: White, Black, Tile Red, Dusty Grey, Regatta, Morning Glory, Turf Green, Mint Green, Aquamarine, Pewter, Ash Grey, Off White, Antique, Gardenia, Sundance Yellow, Paw Paw, Teenage Pink, Fiesta Red, Golden Brown, Spanish Brown

10/2019

#### EDGECHEM JAMAICA LIMITED

The suggestions recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use of our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.

#### PAGE 2

# **COLOR GLOW PLUS Gloss Oil Paint**

### **COVERAGE RATE**

Approximately 10 m<sup>2</sup> per/L (400 sq. ft/gallon) @:

4.0 mils wet film thickness

2.0 mils dry film thickness (dependent on porosity of surface).

### SURFACE PREPARATION

Surface must be free of dirt, chalk, wax, rust, mildew, fungus and all other foreign substances. Glossy surfaces should be sanded. New or unpainted surfaces such as steel, iron, aluminum and concrete should be primed using appropriate primer. Color Glow Plus Gloss is self-priming on bare wood.

### **APPLICATION**

Stir thoroughly before use. If using a brush or roller thinning is not required. If spraying, reduce by 10% using Edgechem Oil Paint Reducer (1 pint reducer to 1 gallon paint). Paint spatters or drops must be cleaned immediately with the reducer.

### SHELF LIFE

3 years

### **CLEAN UP**

Clean brushes, roller and spray equipment immediately after use with Edgechem Oil Paint Reducer.

EDGECHEM JAMAICA LIMITED

The suggestions recommendations and technical data in this document are based on information we believe to be valid. However, they are offered without guarantee as application and methods of use of our products are beyond our control. We recommend that users evaluate our materials before adopting them for commercial uses. Suggestions for use of our products should not be understood as recommendations that may be used in violation of any patent.