



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 3

T.D.S.

FURNITURE PUTTY

DESCRIPTION

Edgechem Furniture Putty is a Polyester based body putty which is catalyzed with Benzoyl Peroxide (B.P.O. soft tube hardener) to fill and repair imperfections on wooden surfaces such as furniture and toys.

PERFORMANCE FEATURES

- Very fast cure
- Easy to Sand
- Excellent adhesion and filling properties for wooden surfaces.
- Exceptional storage stability.

PHYSICAL PROPERTIES

Colour	:	Blends with Wood-colour
Specific Gravity	:	1.44g
Flash Point	:	22.7 °C (73 °F)
Drying Time		
To Touch	:	5 minutes
To Sand	:	15 minutes

COVERAGE RATE

Approximately 32 square feet per gallon.

SUGGESTED USES

Used for restoring and repair of wooden surfaces such as furniture and toys, also for concealing imperfections on other wooden surfaces.

FURNITURE PUTTY

SURFACE PREPARATION

All loose particles, dust and shavings must be removed from surface.

APPLICATION

Furniture Putty – to the size of an egg – add one (1) inch of B.P.O. hardener (Always knead hardener and mix putty thoroughly to a uniform colour before using). Apply catalyzed Putty to damaged area with clean spreader or putty knife. Build up putty slightly higher than surface to allow for an even, level and proper feather-edging when sanding approximately 15 minutes after application.

SHELFLIFE

1 year

CLEAN UP

Clean up using Edgechem Lacquer Thinner