



EDGECHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

## PRODUCT DATA SHEET

Rev. 2

T.D.S.

### ROAD MARKING PAINT

#### DESCRIPTION

Edgechem Road Marking Paint is an alkyd based, quick drying coating which is durable with excellent adhesion and re-coating capabilities.

#### PERFORMANCE FEATURES

- Quick Drying
- Interior and Exterior use
- Good durability
- Excellent Hiding Power
- Apply with brush, roller or spray

#### PHYSICAL CHARACTERISTICS

Colour	:	White, Yellow, Blue
Density (lb/gal)	:	10.6 ± 0.1
Finish	:	Egg Shell
Viscosity (cP)	:	620 - 1000
Flash Point	:	9 °C
Drying Time (31° and 70% RH)		
To Touch	:	10 minutes (Dependent on temperature and relative humidity)
To Recoat	:	after 1 hour

#### COVERAGE RATE

Varies considerably with method of application and type of surface. One gallon will do a four inch line (120 – 150 meters long.)

## **ROAD MARKING PAINT**

### **SUGGESTED USES**

Edgechem Road Marking Paint is suitable for use on new and previously painted bitumen and concrete roads, runways, parking lot surfaces and traffic lanes in industrial plants.

### **SURFACE PREPARATION**

The surface to be coated must be clean, free from dirt, sand, gravel, oil and grease.

### **APPLICATION**

Stir contents thoroughly before using. If using a brush or roller apply without thinning. If spraying, reduce by 5-10%, with Edgechem Industrial Thinner. The paint will touch dry in 10 minutes and hard dries in 1 hour.

DO NOT apply Road Marking Paint during rainy weather, as this could affect the initial drying and curing of the product.

### **SHELFLIFE**

2 years

### **CLEAN-UP**

This should be done immediately using Edgechem Industrial Thinner.