



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 2

T.D.S.

EDGECHEM MATTE VARNISH

DESCRIPTION

Edgechem Matte Varnish is a high quality polyurethane flat varnish formulated with high performance characteristics, which will give maximum protection to interior and exterior wood surfaces. Edgechem Matte Varnish brushes on easily, flows well and give a smooth, clear-flat finish. This premium quality Flat Varnish will resist the most severe weather conditions and its unique formulation will guarantee a beautiful, long-lasting matte finish.

PERFORMANCE FEATURES

- Interior/Exterior Wood substrates
- Tough and Durable
- Matte/Flat Finish
- Resistant to severe weathering
- Flows well & Easy to apply

PHYSICAL PROPERTIES

Gloss	:	<5 degrees at 60°
Specific Gravity	:	0.91
Flash Point	:	31.6°C (89°F)
Colour	:	Amber
<u>Drying Time @ 25 °C</u>		
To touch	:	2- 3 hours
To recoat	:	16 hours
To Sand	:	16 hours

COVERAGE

Approximately 350 sq.ft./gallon (depends on surface texture and porosity)

EDGECHEM MATTE VARNISH

SUGGESTED USES

For interior/exterior use on wood surfaces such as decks, railings equipment, doors, porches, window sills and furniture where a matte finish is required.

SURFACE PREPARATION

For previously painted surfaces in good condition, sand well with 180 grit sandpaper. Remove all traces of dust before applying varnish.

For surfaces in poor condition, remove all loose and peeling paint, then treat as for natural wood.

For natural wood, sand with 80 grit sandpaper. Wipe free of dust with EdgeChem Oil Paint Reducer.

APPLICATION

Apply a sealer coat of varnish (reduce 10% with Oil Paint Reducer), then apply full body allowing 15-18 hours between coats and sanding with 220 grit sandpaper between coats.

Thin only if necessary with Edgechem Oil Paint Reducer. Do not exceed 10% by volume

SHELF LIFE

2 years

CLEAN UP

Clean up with Edgechem oil paint reducer