



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 3

T.D.S.

EDGECHEM STAIN VARNISH

DESCRIPTION

Edgechem Stain Varnish is a unique combination of a Polyurethane Varnish and a Stain. It is designed for use on new and old wooden surfaces, which affords its user with additional benefits of time, money and satisfaction with its 'two-in-one' properties. Edgechem Stain Varnish provides a rich color with a glossy protection to wooden surfaces, while simultaneously preserving the stain finish that is tough, durable and gives a very attractive finish.

PERFORMANCE FEATURES

- Interior & exterior durable wood finish
- High Gloss
- Resistant to weathering
- Flows well and Easy to apply

PHYSICAL PROPERTIES

Gloss	:	>85 degrees at 60°angle
Specific Gravity	:	0.91
Flash Point	:	35°C (95°F)
Shelf Life	:	1 year
Color	:	Mahogany, Light Oak, Walnut, Dark Oak, Antique Black
Drying Time @ 25 °C		
To touch	:	2 - 4 hours
To recoat	:	14-16 hours

COVERAGE

Approximately 9-10 m²/L (375-425 sq.ft./gallon) depending on surface condition and absorbency

EDGECHEM STAIN VARNISH

SUGGESTED USES

For interior/exterior use on wood surfaces such as decks, railings equipment, doors, porches, window sills, cabinets, etc.

SURFACE PREPARATION

New Wooden Surfaces

Ensure that all holes, cracks and joints are filled with wood filler. Ensure that surfaces are free from dust, dirt, oil, grease and other particles. Sand all surfaces with 240-320 grit sand paper to an even and smooth texture. Blow or wipe away residual dust particles. Apply first coat of stain reduced 10% with Edgechem Oil Paint Reducer (1 pint Oil Paint Reducer per gallon of Stain Varnish). Allow to dry overnight and recoat with 1-2 coats un-reduced Stain Varnish.

Previously Varnished Wooden Surfaces

Remove all traces of dirt and remove grease and oil with a degreaser. Remove all peeling, loose, flaking aged Stain Varnish. Refill all holes, cracks and joints with wood filler. Sand all surfaces with 240-320 grit sandpaper. Blow or wipe away all dust particles. Apply 1-2 coats of Edgechem Stain varnish allowing overnight drying in between coats...

APPLICATION

By Brush or Spray. Supplied ready for use but may be thinned (especially when spraying) with Edgechem Oil Paint Reducer if necessary. Do not exceed 10% by volume.

SHELF LIFE

2 years

CLEAN UP:

Clean up with EdgeChem Oil Paint Reducer