

# TECHNICAL DATA SHEET

## **Urethane Regular Hardener**

#### Description

Urethane Regular Hardener is a medium solids isocyanate hardener designed for use with Edgechem Urethane Super Clear, Automel Enamel and Auto Prime Filler and Automel Super Clear Matte.

#### **Compatible Substrates**

Urethane Super Clear Automel Enamel Auto Prime Filler Edgecheml Super Clear Matte Industrial Quick Dri Enamel

### Preparation

See Technical Data Sheets (TDS) and labels for respective Edgechem products to be used with.

#### Application

See Technical Data Sheets (TDS) and labels for respective Edgechem products to be used with.

#### Mixing

See Technical Data Sheets (TDS) and labels for respective Edgechem products to be used with.

#### **Dry Times**

See Technical Data Sheets (TDS) and labels for respective Edgechem products to be used with.

### Clean Up

See Technical Data Sheets (TDS) and labels for respective Edgechem products to be used with.

## Properties

VOC:	398 g/l or 3.32 lb/gal
Shelf Life:	1 year
Colour:	Clear
Viscosity:	25-35 sec @ 27 $^\circ\!\!\mathbb{C}$

Limitations:

Edgechem products should not be combined with components of other product lines.

#### Precautionary Information:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have hazards of all its parts. Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Follow label directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

#### Medical Response:

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (876)937-3831-4

#### Material Safety Data Sheet:

Material safety data sheet for the Edgechem products named herein can be obtained from Edgechem Jamaica Limited by emailing researchanddev@edgechem.com