



EDGECHEM JAMAICA LIMITED  
18 Carifta Avenue  
Kingston 11, Jamaica  
Tel: (876) 937-3831-4 Fax: 937-3838  
E-mail: [edge@cwjamaica.com](mailto:edge@cwjamaica.com)  
Website: [www.edgechem.com](http://www.edgechem.com)

## PRODUCT DATA SHEET

Rev. 0

T.D.S.

### MATTING PASTE

#### DESCRIPTION

Edgechem Matting Paste is a matting agent formulated to reduce the gloss level in various types of high gloss solvent borne coatings. This Matting Paste can be used to matt/flatten various Edgechem paint products including Industrial enamels, Varnishes and many other compatible products. The use of this matting paste does not compromise the properties of the surface where it is applied.

#### PERFORMANCE FEATURES

- Wide Mixability
- Suitable for Solvent-borne paints
- Contains various fillers with matting properties
- Usually has no negative effect on the properties of the base paint
- Gives final product higher abrasion resistance

#### PHYSICAL PROPERTIES

Colour	:	Grey
Density	:	9.8 – 1.0 lb/gal
Viscosity	:	1790 – 1890 cP

#### COVERAGE RATE

Depend on the matting effect desired.

## **MATTING PASTE**

### **SUGGESTED USES**

Edgechem Matting Paste is suitable for use in solvent-borne paints including Automel Enamel, Quick Dri Industrial Enamel, Color Glow Gloss Paints, Stain Varnish, Marine Varnish, Gloss Wood Lacquer, Super Clear 2011.

### **SURFACE PREPARATION**

As for the topcoat in question without the matting paste added.

### **APPLICATION**

Stir and shake Edgechem Matting Paste thoroughly. Add the stirred and shaken Edgechem Matting Paste to the paint and mix thoroughly. Prepare the mix further as specified for the topcoat in question without the matting paste added. The quantity of Matting Paste will depend on the kind of paint and the gloss grade desired.

In a general way, it is advisable to add between 10-15 % of matting paste, both for changing gloss to satin and satin to matt.

When using matting paste, a decrease in the viscosity of the original paints should be expected and thinning for the application will be minor. Dilution may not be necessary depending on the paint and application. The colour of the paint can also affect the gloss level.

Close the matting paste can immediately after use to prevent the paste from drying out.

### **Special considerations**

If in doubt about the effect of adding Edgechem Matting Paste or any possible influence on the properties and/or quality of a paint product, always carefully carry out a test beforehand.

Edgechem Matting Paste is not suitable for use in waterborne paint products.

### **SHELF LIFE**

1` years

### **CLEAN UP**

Clean up with Edgechem Lacquer Thinner

10/2013

**EDGECHEM JAMAICA LIMITED**