



TECHNICAL DATA SHEET

Urethane Super Fast Hardener

Description

Edgechem Urethane Super Fast Hardener is a medium solid isocyanate hardener designed for super-fast drying with Edgechem Clearit, Urethane Super Clear, Automel Enamel and Auto Prime Filler.

Compatible Substrates

EdgechemClearit,
Urethane Super Clear
Automel Enamel
Industrial Quick Dry Enamel
Auto Prime Filler

Preparation

See technical data sheet (TDS) and labels for respective Edgechem product to be used with

Application

See technical data sheet (TDS) and labels for respective Edgechem product to be used with

Mixing

See technical data sheets (TDS) and labels for respective Edgechem products to be used with

Dry Times

See technical data sheets (TDS) and labels for respective Edgechem products to be used with

Clean Up

Same as above

Properties

VOC	-413 G/L or 3.45 lbs/gal
Shelf life -	1 year
Colours -	Clear
Viscosity -	25-35 secs @ 27°C

Limitations:

Edgechem products should not be combined with components of other product lines.

Precautionary Information:

The contents of this package may have to be blended with other components before the product can be used. Before opening the packages, be sure you understand the warning messages on the labels of all components, since the mixture will have hazards of all its parts. Spray equipment must be handled with due care and in accordance with manufacturer's recommendations. Follow label directions for respirator use. Wear eye and skin protection. Observe all applicable precautions.

Medical Response:

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (876)937-3831-4

Material Safety Data Sheet:

Material safety data sheet for the Edgechem products named herein can be obtained from Edgechem Jamaica Limited by emailing researchanddev@edgechem.com