



EDGECHEM JAMAICA LIMITED
18 Carifta Avenue
Kingston 11, Jamaica
Tel: (876) 937-3831-4 Fax: 937-3838
E-mail: edge@cwjamaica.com
Website: www.edgechem.com

PRODUCT DATA SHEET

Rev. 2

T.D.S.

SUPER GLOSS SPAR VARNISH

DESCRIPTION

Edgechem Super Gloss Spar Varnish is a high gloss varnish designed for exterior and interior use on wooden surfaces and metal.

PERFORMANCE FEATURES

- High gloss
- High build

PHYSICAL PROPERTIES

Gloss	:	>85% at 60°
Specific Gravity	:	0.91
Flash Point	:	31.6°C (89°F)
Colour	:	Clear lavender
Drying time		
To touch	:	1½ - 2 hours
To re-coat	:	6-8 hours
Hard dry	:	Overnight

SUGGESTED USES

For use on interior and exterior wooded surfaces.

SURFACE PREPARATION

Sand surface properly and remove dust by blowing with air. Surface should be cleaned with Edgechem Oil Paint Reducer.

SUPER GLOSS SPAR VARNISH**APPLICATION**

The first coat of Varnish should be thinned 5% with Oil Paint Thinner when applying to bare wood, use full bodied over Sanding Sealer or aged coatings. Second coating should be applied full bodied.

SHELFLIFE

2 years

CLEAN UP

Clean up with Edgechem Oil Paint Thinner